

Interface FLOR | Galleria Antron

**PRODUKTDATEN**

<b>Konstruktion</b>	Fusion Bonded Printed Tile	<b>Style Number</b>	<b>5428050400</b>
<b>Polfasermaterial</b>	100% Polyamid	<b>Klassifikation</b>	EN 1307 33 Heavy Contract
<b>Poleinsatzgewicht</b>	950g/m <sup>2</sup> ± 5%	<b>Brandverhalten - Radiant panel</b>	(EN ISO 9239/1) Euroclass Bfl S1 (EN ISO 13501)
<b>Gesamtgewicht</b>	4950g/m <sup>2</sup> ± 5%	<b>Hot Metal Nut</b>	Pass, low radius of effects of ignition (BS 4790)
<b>Polschichtdicke</b>	4.0 mm ± 0.3 mm	<b>Stuhlrollenprüfung</b>	≥ 2.4 (EN 985)
<b>Gesamtdicke</b>	7.9 mm ± 0.5 mm	<b>Dimensionsstabilität</b>	≤ 0.1% (ISO 2551)
<b>Teilung x 10 cm</b>	43.4	<b>Durchgangswiderstand</b>	5 x 10 <sup>5</sup> Ω >< 1 x 10 <sup>9</sup> Ω (ISO 10965) (IBM)
<b>Noppenzahl/m<sup>2</sup></b>	119,350 ± 5%	<b>Lichtechtheit</b>	5-6 (ISO 105/B02)
<b>Rückenkonstruktion</b>	Glasbac	<b>Fliesen / Karton</b>	16 - 4m <sup>2</sup> (50 x 50 cm ± 0.1%)

CE  
06  
0338-CPD-1001

EN 1307

MicroBleed  
16027 23dB  
ENF 10001  
ENF 00078  
Intersept  
Environmental Probe Scheme  
Certificate Number ENP 311



**Mission Zero:**  
our promise to eliminate  
any negative impact our company  
may have on the environment  
by the year 2020.

[www.interfaceflor.eu](http://www.interfaceflor.eu)

Technische Änderungen vorbehalten